Model identifier(s): 5860	0/58601/	58602/	58603	3/99386/99387/99388/99389					
Indirect heating function	ality: [N	o]							
Direct heat output: 4.2 (kW)									
Indirect heat output: N/A	(kW)								
Fuel					Space heating emis		ssions		
					(Ñ)				
Select fuel type		[gaseous]		G30	7.6 [mg/ kWh _{input}]		(GCV)		
Item		Value	Unit	Item	Symbol	Value	Unit		
Heat output				Useful efficiency (NCV)					
Nominal heat		4.2	kW	Useful efficiency at nominal		100	0/		
output	P _{nom}			heat output	$\eta_{th,nom}$	100	%		
Minimum heat	В	N/A	kW	Useful efficiency at minimum	$\eta_{\text{th,min}}$	N/A	%		
output (indicative)	P _{min}			heat output (indicative)					
Auxiliary electricity consumption				Type of heat output/room temperature control (select one)					
At nominal heat		N/A	kW	Single stage heat output, no room temperature					
output	el _{max}			control	•		[No]		
At minimum heat		NI/A	kW	Two or more manual stages, no	oom				
output	el _{min}	N/A		temperature control			[Yes]		
In standby mode	el _{SB}	N/A	kW	With mechanic thermostat room	temperature				
in standby mode	GISB	IN/A		control			[No]		
				ith electronic room temperature control			[No]		
				With electronic room temperature control plus					
				day timer			[No]		
				With electronic room temperature control plus			[NI=1		
				week timer			[No]		
				Other control options (multiple selections possible			·		
				Room temperature control, with presence detection			[No]		
				Room temperature control, with open window			[No]		
				detection					
				With distance control option			[No]		
				With working time limitation			[No]		
				With working time limitation With black bulb sensor			[No]		
Permanent pilot flame power requirement				WILL DIACK DUID SELISUI			[No]		
Pilot flame power	1								
requirement (if	P _{pilot}	0.17	kW						
applicable)	- pilot								
Contact details	MILLARCO INTERNATIONAL A/S Rokhøj 26 - 8520 Lystrup - Denmark Tel: +45 8743 4200								
(*) NOx = nitrogen oxide	(*) NOx = nitrogen oxides								
	<u></u>		· <u></u>			<u></u>			

The seasonal space heating energy efficiency η _S						
Item	Symbol	Value	Unit			
The seasonal space heating Energy efficiency in active mode	ηs,on	100	%			
Correction factor (F1)	1	0	%			
Correction factor (F2)	/	1.0	%			
Correction factor (F3)	/	0	%			
Correction factor (F4)	/	0	%			
Correction factor (F5)	/	2.02	%			
Biomass label factor	BLF	1	/			
The seasonal space heating energy efficiency ηs	ης	88.98	%			
Energy Efficiency Index (EEI):	EEI	88.98	%			
Energy efficiency classes	Α					